

## Self-assembled Diphenylalanine Microtubes: Emerging Properties and Applications

F. Salehli<sup>1</sup>, S. Kopyl<sup>2</sup>, P. Zelenovskiy<sup>3</sup>, A. Nuraeva<sup>3</sup>, S. Vasilev<sup>3</sup>, A. Esin<sup>3</sup>, V. Shur<sup>3</sup> and A.L. Kholkin<sup>2\*</sup>

<sup>1</sup>Department of Physical Engineering, Istanbul Technical University, Istanbul, Turkey, 34669

<sup>2</sup>Department of Physics and CICECO – Aveiro Institute of Materials, University of Aveiro,  
Aveiro, Portugal, 3810-193

<sup>3</sup>School of Natural Sciences and Mathematics, Ural Federal University,  
Ekaterinburg, Russia, 620000

\*Andrei Kholkin: kholkin@ua.pt

The diphenylalanine (FF) is one of the self-assembling peptides which have recently become a focus of intensive research in the field of nanomaterials because they can spontaneously form fascinating discrete and well-ordered structures: nano- and microtubes, nanospheres, nanofibrils, and hydrogels [1]. FF peptide tubes (PTs) possess unique biological and physical properties such as inherent biocompatibility, high aspect ratio and remarkably rigid structure [1]. Strong piezoelectricity found recently in FF adds a new important functionality useful for the development of sensors, actuators and micromechanical systems [2]. Piezoeffect was found to be sufficiently stable being strongly dependent on the chemical modifications and synthesis conditions [3]. Thus, biocompatible, lightweight and highly mechanically stable FF PTs are an attractive material for the fabrication of future generation of resonance biosensors [4].

In this work, we report the results of our recent studies on the growth and characterization of FF PTs by piezoelectric, pyroelectric and dielectric methods [5-7]. A method of growth of large (mm size!) microtubes consisting of individual FF nanotubes was developed [5] and thus the tubes could be transferred and mounted on structured substrates. Piezoelectric properties were then evaluated either by the resonance method or by quantitative Piezoresponse Force Microscopy (PFM). We show that the entire piezoelectric matrix of diphenylalanine peptide microtubes could be measured if the proper arrangement of the tubes is constructed [6]. Piezoelectric coefficients were sufficiently high and comparable to those of ZnO and LiNbO<sub>3</sub>. Also a significant pyroelectric effect was found in FF microtubes grown by this method [7]. Low temperature phase transitions were rigorously studied by dielectric spectroscopy. Several anomalies were found in the temperature range 100-350 K accompanied by the strong dielectric relaxation. Unusual behavior of the dielectric relaxation times observed in this work was attested to the relaxation of water molecules in FF PTs nanochannels. At low temperature two groups of water molecules coexist near the hydrophilic carboxyl groups and in the core of nanochannels having completely different dynamics leading to structural changes. A crucial role of nanoconfined water in emerging physical properties of FF peptide tubes will be discussed in this work.

Acknowledgments: This work was supported by the FCT project TUBITAK/0006/2014.

[1] Zelenovskiy P, Kornev I, Vasilev S, Kholkin AL, Phys. Chem. Chem. Phys. (2016) 18, 2968.

[2] Kholkin AL, Amdursky N, Bdikin I, Rosenman G, Gazit E. ACS Nano (2010) 4, 610.

[3] Heredia A, Bdikin I, Kopyl S et al. J. Phys. D: Fast Track Comm. (2010) 43, 462001.

[4] Bosne ED, Heredia A, Kopyl S et al. Appl. Phys. Lett. (2013) 102, 073504.

[5] Nuraeva A, Vasilev S, Vasileva D et al Cryst. Growth Des. (2016) 16, 1472.

[6] Vasilev S, Zelenovskiy P, Vasileva D et al. J. Phys. Chem. Sol. (2016) 93, 68.

[7] Esin A, Baturin I, Nikitin T et al, Appl. Phys. Lett. (2016) 109, 142902.